



Technical drawings of a beam cross-section and side view. The top left shows a cross-section of a rectangular beam with height H . The bottom left shows a side view of the beam with length L . The right side shows a 3D perspective view of the beam with a triangular support at the bottom right corner.

Technical drawing of the 'Système de chauffage à infrarouge' (Infrared heating system) showing components and installation details.

Components:

- EMBOUT (Bracket)
- SUPPORT DE MONTAGE (Mounting support)
- DISQUES DÉFONÇABLES (Removable discs)
- CONDUCTEURS DE L'APPAREIL (Device conductors)
- APPAREIL DE CHAUFFAGE (Heating device)

Installation Details:

- VIS DE MISE À LA TERRE (Grounding screws)
- PLAFOND (Ceiling)
- PLANCHER (Floor)
- Au moins 1,8 m (6ft.) du plancher (At least 1.8 m (6ft.) from the floor)

COVE MODÈLE	PUISSANCE	L	H	I	P
632C	585 W	83,8 cm (33 po)	17,8 cm (8 po)	2,9 cm (1 ¹⁸ / ₈ po)	14 cm (5,5 po)
645C	825 W	116,8 cm (46 po)	17,8 cm (8 po)	2,9 cm (1 ¹⁸ / ₈ po)	14 cm (5,5 po)
945C	1000 W	116,8 cm (46 po)	25,4 cm (10 po)	2,9 cm (1 ¹⁸ / ₈ po)	19,1 cm (7,5 po)
1445C	1500 W	116,8 cm (46 po)	38,1 cm (15 po)	2,9 cm (1 ¹⁸ / ₈ po)	25,4 cm (10 po)

Figure 1: Schéma de câblage standard

Toute autre réparation devrait être effectuée par du personnel qualifié ou un électricien fiable.

CONSERVER CE MODE D'EMPLOI